

Jett Sett

Basictm

50 grams
Commercial Sample



DIRECTIONS:

- 1) Heat water in a hot pot, electric pickler, or in the microwave oven (the amount of water should be enough to cover the surface area of the amount of **Jett Sett Basic**tm material that is required).
- 2) Use a thermometer to ensure that the water is not heated more than 75 °C.

DO NOT HEAT MORE THAN 75 °C,

or the material might lose its properties!

- **3)** Pour the desired amount of **Jett Sett Basictm** into the heated water. After a few minutes it will soften. As the materials heats and softens it will turn from white colour to semi-transparent.
- **4)** Use tweezers or tongs to remove the heated material from the hot water. Use caution in handling the heated material and squeeze **Jett Sett Basic**tm with your hands to remove excess water.
- **5)** Form the material into the desired shape or fill it into the fixture, which will hold your small parts (e.g. stone setting, engraving etc).
- **6)** Allow the material to harden. Submerse it into cold water; place it in the fridge or use you mold chiller to expedite the hardening process.

Jett Sett

from

COOL TOOLZ

Nagesh: 99000 44332

73-C-2, Ground Floor,

Electronics City, Bangalore, Karnataka 560100

cooltoolzblore@gmail.com

cooltoolz.co.in